
HydraEdge 3 Piece | Permeable | Smooth Face

60 MM (2 3/8")

Coverage (ft²)

Layers

Pieces



Full

124

3,106

10

300



PATTERNS

Ř

Layer

12.4

306

1

30

	ĽĽ	Ц	I II.	
	╷╴╷			
	╘			
	ĻΪ	П	ГП,	
	╷╴╷			4
	╘			
				4
	h			
	· · · · ·	П.	<u> </u>	11

Running Bond

Lg Rec 1 | Sm Rec 1 | Sm Sq 1

		┍╞╧┷┨╤	
	T		
			╘┥╻┝┷┇
╞┥┯┷			╷╧╧┷┨

PALLET OVERVIEW

PALLET SPECIFICATIONS

Weight (lbs) (does not include pallet weight)

PERMEABILITY

Half

62

1,578

5

150

Joint Width: 12mm % of Surface Opening: 8.5% Infiltration Rate: > 900 in/hr

Modular Lg Rec 1 | Lg Sq 1 | Sm Sq 1

	Ŧ
	-
	_
	-
	Τ
┯┷╼┥╞╧┱┷┯┥	F
	┣
	L
-	
	_
	Т
	1
	-
 	-

Random Lg Rec 2 | Lg Sq 2| Sm Sq 1

FINISHES



Lowcountry Paver Products meet & exceed ASTM C 936 requirements.